

Technical Data Sheet

200-230

<u>Test</u>	<u>UoM</u>	<u>Method</u>	<u>Min</u>	<u>Max</u>	<u>Typical</u>
API Gravity @ 60°F		D4052			62.2
Specific Gravity @ 20/20°C		D4052	0.7080	0.7680	0.7305
Color, Saybolt		D156	25		30
Flash, TCC	°F	D56			32
Distillation, IBP	°C	D86	85		97
Distillation, 10%	°C	D86		102	99
Distillation, 50%	°C	D86		107	100
Distillation, 90%	°C	D86		121	105
Distillation, EP	°C	D86		143	110
Water Content	ppm	D1533		500	17
Benzene Content, ppm		CCVM			< 1
Aromatics	Wt. %	D6729		1.00	0.10
Kauri-Butanol Value		D1133	30.0	45.0	32.5
Doctor Test		D235			Negative
Acidity			Pass		Pass
Spot Test					Negative
Non-Volatile Matter	g/mL	D1353		0.005	0.00
Acrylic Crazing Test			Pass		Pass
Appearance		Visual	B/C		B/C
Copper Corrosion		D130	Pass		Pass
Odor		Organoleptic	Pass		Pass

Extra Notes: Product meets TT-N-95 B Type I & II

These specifications are typical and represent the quality of our product in general. The information herein is to assist customers in determining whether our product is suitable for their applications. Our product is intended for sale to industrial and commercial customers. We recommend that customers inspect and test our products before use and satisfy themselves as to content and suitability. We warrant that our products will meet our written specification. Nothing herein shall constitute any other warranty expressed or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. Health and safety information, as well as safe handling instructions are available through our Safety Data Sheet for this product. For more information about our products, please call (323)245-2345.