

Technical Data Sheet

Xylene

Property	Unit	Method	Min	Max
Density @ 59°F (15°C)	kg/m3	ASTM D4052	865	875
Specific Gravity @ 60°F		ASTM D1298	0.865	0.875
Appearance		Visual	Clear & Bright	
Flash Point (Pensky-Martens)	°F (°C)	ASTM D93	75 (24)	
Non-Aromatic Hydrocarbons	Wt. %	ASTM D6563		1
Aromatics	Weight %	ASTM D6563	99	
Benzene Content	Wt. %	ASTM D6563		0.03
Ethyl Benzene	Wt. %	ASTM D6563		20
Bromine Index	mgBr/100g	ASTM D5776	Report	
Water Content	ppm	ASTM E1064	Report	
Toluene	Wt. %	ASTM D6563		0.5
Distillation @ 760 mm/hg	°C	ASTM D850		5
Color, Pt-Co scale	-	ASTM D1209		10
C9 and Higher Boiling Aromatics Hydrocarbons	Wt. %	ASTM D6563		1
Cumene	Wt. %	ASTM D6563	Report	
Para-Xylene	Wt. %	ASTM D6563	18	
Meta-Xylene	Wt. %	ASTM D6563	Report	
Ortho-Xylene	Wt. %	ASTM D6563	Report	
Acidity	-	ASTM D847	Pass/Fail	
Acid wash color	-	ASTM D848		4
Copper Corrosion	-	ASTM D849	Pass (1A or 1B)	
Initial Point	°F(°C)	ASTM D850	276.8 (136)	
Dry Point	°F(°C)	ASTM D850		289.4 (143)
Sulfur Content (D5453)	ppm	ASTM D5453		1

These specifications are typical and represent the quality of our product in general. The information herein is to assist customers in determining whether our product is suitable for their applications. Our product is intended for sale to industrial and commercial customers. We recommend that customers inspect and test our products before use and satisfy themselves as to content and suitability. We warrant that our products will meet our written specification. Nothing herein shall constitute any other warranty expressed or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. Health and safety information, as well as safe handling instructions are available through our Safety Data Sheet for this product. For more information about our products, please call (323)245-2345.